



# MACHETE AUTOMATIC MLR

OPERATION'S MANUAL



The total or partial reproduction of this manual  
is prohibited by any means, whether printed or electronic;  
without the prior, express and written authorization of the author.

---

## **MACHETE AUTOMATIC MLR**

OPERATION'S MANUAL

---

## INDEX

GENERAL SAFETY INSTRUCTIONS .....	4
CAUTION .....	5
ELECTRICAL INSTALLATION .....	6
COMPONENTS .....	7
OPERATING INSTRUCTIONS .....	8
CLEANING AND MAINTENANCE .....	10
LUBRICATION .....	11

## GENERAL SAFETY INSTRUCTIONS

**WARNING:** To reduce the risk of injury, read all instructions properly. Failure to follow the instructions listed below can cause electric shock, fire, serious injuries, mutilation, and/or damage to the equipment.

### A. SAFETY IN THE WORK AREA.

- \* Keep the work area clean and lit. Crowded or dark areas lead to accidents.
- \* Keep children, customers, and non-company personnel away from the electrical or mechanical operation of the equipment.
- \* It is recommended to have a minimum space of one meter or three feet around the machine for safety measures and to optimize work.

### B. ELECTRICAL SAFETY.

- \* The connections of the machinery must be adapted to the power outlets.
- \* Do not use adapters for the switches: since you run the risk of receiving an electric shock.
- \* Do not expose the switches and/or electrical connections to rain or humidity. If water enters these elements, there is a risk that they will break down or suffer an electric shock.
- \* Use cable in a single piece, if there are joints in the connections these can produce a short circuit.
- \* Do not expose cables or electrical connections to heat, oil, sharp edges, or moving parts, as damaged cables can cause electric shock or short circuits.

### C. PERSONAL SAFETY.

- \* Do not operate the equipment if you are tired, or under the influence of alcohol or drugs.
- \* Wear appropriate clothing, do not wear loose clothing, necklaces, earrings, or watches, if you have long hair wear a tie to keep it up.
- \* Do not climb on the structure of the machine for any reason, falls or injuries may occur.
- \* Avoid using headphones, cell phones, or any other equipment that works as a distraction to the operator.
- \* Make correct use of personal protective equipment if any maintenance is to be carried out on the machine.
- \* If any change is made to the model or component of the equipment, be it electrical or mechanical related, it must be de-energized and stop the machine completely to avoid accidents.
- \* Keep limbs away from all moving parts.

# MACHETE AUTOMATIC MLR OPERATION'S MANUAL

---

## CAUTION

The following symbols indicate the safety measures that must be taken before and after starting up the equipment.



**TAKE CARE OF YOUR HANDS** Hands should not be inserted while the machine is working.



**ELECTRICAL RISK** In which you can suffer electric shocks if you do not comply with the electrical safety provisions.



**GEAR RISK** Keep your hands away from the chains and gears of the machine.

# MACHETE AUTOMATIC MLR

## OPERATION'S MANUAL

### ELECTRICAL INSTALLATION

Verify that the electrical connection is 110v. No short circuits, no loose or bare wires.

Ensure that all cables are isolated and without contact, and check contactors and switches are in good condition.

It is recommended to use a 12 gauge cable for the installation of the Automatic Gorditas MLR.




ELECTRICAL INSTALLATION	
<b>A</b>	110V electrical installation
<b>B</b>	12 gauge cable (conduit cable).

# MACHETE AUTOMATIC MLR

## OPERATION'S MANUAL

### COMPONENTS



# MACHETE AUTOMATIC MLR

## OPERATION'S MANUAL



1

Check that the straps rotate freely



2

Make sure that the wire is tight and not broken



3

Place the cutter on the base, and verify that it is correctly installed and secured



4

Spray grooves and straps with water to remove excess product



5

Plug the machine into an electrical outlet



6

Push the engine start button

# MACHETE AUTOMATIC MLR OPERATION'S MANUAL



7

Add the dough to the rollers



8

Adhere the dough curtain to the front roller



9

Release the cutter lever



10

Check that the dough unsticks correctly



11

Adjust the gordita thickness by turning the adjustment knobs (clockwise to make the tortilla thinner, and counterclockwise to make it thicker) Lower the clutch lever when you obtain the desired thickness



12

Check the shape, size, and thickness of the machete

## CLEANING PROCEDURE

WARNING: Cleaning both the rollers and the base must be done with the machine completely stopped to avoid accidents such as crushing.

### FRONT ROLLER CLEANING

1. Remove the dough residues with your hands from the front roller at total stop.
2. Turn the machine on again to change the position of the roller, turn off the machine and proceed with cleaning. You must carry out this action as many times as necessary to complete the cleaning of the roller.
3. Clean the cable tie grooves with a plastic bristle brush to prevent the build-up of mass that may break the wire when it dries.
4. Wipe the remaining dough from the top of the roller with a damp cloth.
5. After removing the dough residues from the roller, there will be a leftover.
6. Spread a little water after removing the remaining dough to complete the cleaning of the roller.
7. Clean the roller with a dry cloth after spreading water over it to remove excess moisture.

### CLEANING THE REAR ROLLER

8. Pour a little water and wipe with the cloth to remove the dough residue.

NOTICE: You will need to turn on the machine to change the position of the rollers as many times as necessary to clean them correctly.

9. After cleaning the two rollers on the front and back, you should clean the upper part of the stainless steel roller with a damp cloth.
10. Use a damp cloth to clean the base of the bench and remove clumps from the swing mesh with a wire brush.

## MAINTENANCE

Clean the machine before and after using it.

The duration of the spare parts will depend on the preventive maintenance and care taken to the machine.

The more frequently this maintenance is done, the parts will have a longer life.

# MACHETE AUTOMATIC MLR

## OPERATION'S MANUAL

---

### LUBRICATION


The following table shows the parts, the type of lubricant, and the frequency with which the machines and their parts must be lubricated.

PART	LUBRICANT	PERIOD
Chains	BAT 3 Grease	3 times per week
Bearings	BAT 3 Grease	Every 3 days
Gears	SAE 40 Oil	Every week
Slide bronze bushing	BAT 3 Grease	3 times per week

# MACHETE AUTOMATIC MLR

## OPERATION'S MANUAL

The following figures show the schematic location of the parts that require lubrication.



The following table shows the type of lubricant to put in all parts of the machine.

LUBRICANT
A) SAE 40 Oil
B) BAT 3 Grease



## **HEADQUARTERS**

AV. INDUSTRIAS #3665, ZONA INDUSTRIAL  
CP 78395 SAN LUIS POTOSÍ, SLP. MÉXICO



444 127 11 80



444 129 29 79

[info@manufacturaslenin.mx](mailto:info@manufacturaslenin.mx)

[MEXICANTORTILLAMACHINE.COM](http://MEXICANTORTILLAMACHINE.COM)